

GUSPRO GP SERIES SPECIFICATIONS

Model GP	Usable Over Cart Dimensions Inside Clear Dimensions (Inches)			Inside Dimensions (Inches)			Design Load* Capacity lbs	Cart Load Capacity lbs	Thermal Oxidizer Capacity lbs./hr.	Fuel Requirements 6 - 8" WC Natural Gas		Approximate Shipping Weight lbs. / Kg
	Width	Depth	Height	Width	Depth	Height				Max. CFH	Average Usage CFH	
202018X	20	20	18	24	24	30	800	2,400	5	400	240	2300 / 1045
324036	32	40	36	36	48	53	1,000	3,600	17	700	420	4000 / 1815
402420X	40	24	20	46	30	34	1,000	2,400	13	550	360	5500 / 2500
404836	40	48	36	46	54	48	1,500	3,600	21	700	420	5650 / 2563
484040	48	40	40	54	48	65	3,000	3,600	30	1250	800	8000 / 3630
247218	24	72	18	28	76	34	800	2,400	5	700	420	5000 / 2268
2412018	24	120	18	28	124	34	800	3,600	5	700	420	6000 / 2722
2424018	24	240	18	38	146	34	8,000	6,000	5	2,000	1,500	9000 / 4082

"X" indicates model with legs for workbench height.

AGA and CGA approved

Specifications are subject to change without notice.

* Design Load based on load that can be brought up to cleaning temperature in under one hour.



280 Grand Avenue East
Chatham, Ontario
Canada N7L 4K1
Tel (519) 352-4550
Fax (519) 352-7676
Toll Free: 1-888-648-7776
Toll Free Fax: 1-800-667-8742



E-mail: guspro@guspro.com

Visit us on the web:
www.guspro.com

* Contact GUSPRO for a no-charge cleaning evaluation

* Free sample processing may be available

* Contact GUSPRO for details